

FIRENOCK A style



Firenock "A" style nock will fit most common slim diameter arrow shafts with ID (Internal Diameter) of 0.202" - 0.204":

- Beman:** Team REALTREE® MFX™,
Classic MFX™,
BLACK MAX™,
MAX-4™.
- Carbon Xpress:** CX Edge™,
CX Edge™ Hunter.
- Easton:** A/C Super Slim,
ST Axis Full Metal Jacket,
ST Axis Full Metal Jacket Camo,
ST Axis Full Metal Jacket Dangerous Game,
ST Axis Realtree APG,
ST Axis Mossy Oak Obsession,
ST Axis,
ST Axis Junior.
- Trophy Ridge:** Crush,
Blast,
Hailfire,
Wrath

Warning: Firenock must make multiple contact points with the inside wall of the arrow in order to function properly. Presence of uni-bushing while using Firenock will void all warranty.

Product associated with A style Firenock

- Nocks Packs (5):** A1, A3(R, G, B), AT, AU
Nocks (4): AB, AC, AG, AR
Practice Weight (1): PA
O-ring (2): OA, OB
End Caps (1): XA
Circuits (12): NB, NC, NG, NO, NR, NY, KB, KC, KG, KO, KR, KY
Battery (2): BR, BL
Bow Fishing (0):