

FIRENOCK E style



Firenock "E" style nock will fit most common medium diameter arrow shafts with ID (Internal Diameter) of 0.227" - 0.232":

Arrow Dynamic: Nitro Stinger (ID: 0.211")*
Easton: ACC Pro Hunter (ID: 0.227")
A/C/C 3-49/390 (ID: 0.230")
A/C/C 3-39/390 (ID: 0.220")*
A/C/C 3-28/390 (ID: 0.205")*
ST Carbon Excel
ST Epic Realtree HD Green
ST Epic Jr
ST Epic
Gold Tip: CAA .400 (ID: 0.232")
High Country: Speed Pro (ID: 0.233")

* Shave ridges of nock to fit smaller diameter shafts, can be as small as 0.205"

Warning: Firenock must make multiple contact points with the inside wall of the arrow in order to function properly. Presence of uni-bushing while using Firenock will void all warranty.

Product associated with E style Firenock

Nocks Packs (5): EI, E3(R, G), ET, EU
Nocks (3): EC, EG, ER
Practice Weight (1): PE
O-ring (2): OE, OB
End Caps (1): XE
Circuits (12): NB, NC, NG, NO, NR, NY, KB, KC, KG, KO, KR, KY
Battery (2): BR, BL
Bow Fishing (0):