

FIRENOCK S style



Firenock "S" style nock will fit most common standard diameter arrow shafts with ID (Internal Diameter) of 0.242" - 0.246":

- Arrow Dynamic:** .395 Mag
- Beman ICS:** Hunter Elite, Hunter, Hunter Junior, Venture, Beman 9.3, Energy
- Cabela's:** Carbon Hunter, Stalker Extreme Carbon, Outfitter Series
- Carbon Xpress:** Aramid KV, Mayhem, Maxima Hunter, Maxima, Maxima 3D-Select, Terminator Hunter, Terminator XP Selecty, Terminator Select, Terminator Select Hunter, Terminator Lite, Terminator Lite Hunter, Terminator Lite Select, Carbon Rebel, Carbon Rebel Hunter, Piledriver, Pradator II, Thunderstorm SE, Thunderstorm, Heritage
- Carbon Impact:** Stealth XLT, Trophy Hunter, Carbon youth
- Carbon Tech:** Cheetah, Panther, Rhino, Whitetail
- Easton:** LightSpeed, PowerFlight, *A/C/C 3-60/340**
- Forge:** Extreme Kevlon
- Gold Tip:** Pro Hunter, XT Hunter, Expedition Hunter, Falcon, Traditional XT, Traditional Hunter, Big Game 100+, Ted Nugent Signature, Velocity, *CAA .350**
- High Country:** Speed Pro
- PSE:** Carbon Force, X-Weave, X-Weave Pro
- Red Head:** Carbon Fury, Carbon Maxx, Carbon Supreme, Carbon Hunter
- Scout Mountain Equip.:** Epsilon Arrows
- Vapor:** Predator, Predator Pro, Hunter, Hunter Pro, Pro Black, Pro Whitetail, Whitetail, *Carbon Alumium .400**, Carbonwood, Wayne Carlton Signature, Vapor Jets
- Victory:** V-Force, V-Force HV

** Shave off all ridges of the nock to fit due to its 0.240" internal diameter.*

Product associated with S style Firenock

- Nocks Packs (8):** S1 (R, G), S3 (R, G, B), ST, SU, SZ
- Nocks (9):** SB, SC, SG, SO, SP, SR, SS, SW, SY
- Practice Weight (1):** PS
- O-ring (2):** OS, OB
- End Caps (1):** XS
- Circuits (18):** HB, HC, HG, HO, HR, HY, IB, IC, IG, IO, IR, IY, TB, TC, TG, TO, TR, TY
- Battery (2):** BR, BL
- Bow Fishing (2):** BF, BI